


K50L2 and K30L2

Bolder Indication for Everyone, Anywhere

- Simplified ordering and design
- Reliable performance in harsh environments
- Improved production efficiency





Give Your Equipment a Voice





Audible options (50 mm models only)



Avoid nuisance maintenance and replacement expense



Hear status information directly



Rely on performance in washdown and humid environments



Improve quality, accelerate training and increase production



Select compliant models for use in food and beverage processing



Consolidate controller outputs; get red, green, and yellow from two outputs instead of three





Bolder Indication for Everyone, Anywhere




Seven colors now available in one housing

- Get seven colors via only three inputs
- Save controller outputs and wiring
- Improve production efficiency through enhanced visual management
- Install wherever you need indication to improve communication and productivity
- Standardize to simplify ordering and spare parts
- Collaborate with Banner on custom models




Limitless Capabilities with IO-Link


- Universal connection
- Millions of color options
- Intensity control
- Animation options
- Drop-in installation
- Simplified wiring







K30L2 Example Model Number: K30L2RGB7Q



* Audible models not available in FDA-grade material

- ** Integral QD not available in FDA-grade material
- † IO-Link models not available with integral cable

Power

Operating

Conditions Construction

Environmental

** Integral QD not available

in FDA-grade material

K50L2: 10 to 30 V dc; 220mA Max. at 10 V dc; 100mA Max. at 30 V dc K30L2: 10 to 30 V dc; 60mA Max. at 10 V dc; 30mA Max. at 30 V dc

Blank = 2 m Integral Cable

Q = Euro Integral QD**

QP = Euro Pigtail QD

-40 to 50 °C

Polycarbonate

K50L2: Standard: IEC IP66/IP67/IP69K Standard Audible: IEC IP50 Sealed Audible: IEC IP66/IP67/IP69K

K30L2: IEC IP66/IP67/IP69K



Certifications

Rating





K50L2

ø 50.0 mm

ø 30.0 mm



SMBAMS22P

58 mm











Controllers



SMB30SC

SMBAMS22RA



Elevated Mounting

For more information go to bannerengineering.com

M12/Euro-Style Cordsets Straight connector models listed; for right-angle, add RA to the end of the model

(example, MQDC1-506RA)

Washdown Cordset (IP69K)

Straight connector models

MQDC-406 2 m (6.5') MQDC-415 5 m (15') MQDC-430

9 m (30')

MQDC1-506 2 m (6.5') MQDC1-515 5 m (15') MQDC1-530 9 m (30')

5-Pin

M12/ Euro-Style

5-Pin

MQDC-WDSS-0506 2 m (6.5') MQDC-WDSS-0515 5 m (15') MQDC-WDSS-0530 9 m (30')



SMB22A

